FLEX		EA39 20	24		BUILT FOR BOWLING
Oil Pattern Distance Forward Oil Total Tank Configuration	12.6 mL Reverse	Brush Drop Oil Total 12. Conditioner Your	.45 mL Vo	l Per Board Iume Oil Total nk B Conditioner	50 ul 25.05 mL Your choice
START STOP LOADS SPED CI 1 4L 4R 1 18 2 5L 5R 1 18 3 6L 6R 2 18 4 8L 8R 2 18 5 10L 10R 2 22 6 11L 11R 2 22 7 2L 2R 0 26 8 2L 2R 0 26	31 0.0 2.5 2.5 15 58 2.5 7.6 5.1 29 50 7.6 12.7 5.1 25 42 12.7 18.9 6.2 21	50 50 00 00		15	15 50 53 53
START STOP LOADS SPEED C 1 2L 2R 0 30 2 11L 11R 1 26 3 9L 9R 2 26 4 7L 7R 2 22 5 5L 5R 2 18 6 4L 4R 1 18 7 3L 3R 1 14 8 2L 2R 0 10	46 26.4 19.1 -7.3 23 54 19.1 12.9 -6.2 27 62 12.9 7.8 -5.1 31 33 7.8 5.3 -2.5 16	<u>niii</u> 50 50 00 00 50 50 50 0			25 30 35 40 45
Cleaner Ratio Main Mix Cleaner Ratio Back End Mix Cleaner Ratio Back End Dis Buffer RPM: 4 = 720 3 = 5 Created by SWEBOWL TK 2 DB use DB 39For use in Sw	tance NA 500 2 = 200 1 = 50 240702 Machines withou	Forward Reverse Combined			5 10 15 20
Item 3L-7L:18L- Description Outside Track Track Zone Ratio 3.39	:Middle Middle Track:Middle	13L-17L:18L-18R Inside Track:Middle 1	18L-18R:17R-13R MIddle: Inside Track 1	18L-18R:12R-8R Middle:Middle Track 1.19	18L-18R:7R-3R Middle:Outside Track 3.39
1500					

--0 -10 11 12 13 14 15 16 17 18 19 20 19 18 17 16 15 14 13 12 11 10 9 s 6 5 4 3 2 1

8 7